



Green is good!

Green Terminology

ASHRAE	American Society of Heating, Refrigerating and Air-Conditioning Engineers. This is the primary organization used in the United States for the design standards in our HVAC systems.
HVAC	Heating, Ventilation and Air Conditioning. HVAC includes the furnace, air conditioning components, fan and ductwork installed in a home.
JUMP DUCT	A flexible, short, u-shaped duct that connects a room to a common space as a pressure balancing mechanism.
LOW E	Low emissivity. Glass is coated with a metallic oxide layer that improves thermal performance. The primary function is to reduce heat gain in the summer and heat loss in the winter.
MANUAL J	The ASHRAE method for calculating residential home cooling loads and the sizing of the system.
MERV	Minimum Efficiency Reporting Value. The ASHRAE standard for filter efficiency. Higher rating is better.
PRESSURE BALANCING	To equalize air pressures between rooms in a house by adjusting air flow in supply and return ducts.
R-410A	Environmentally-friendly refrigerant used in our HVAC systems.
R-VALUE	Resistance – Value. The resistance a material has to heat flow. The higher the R-Value, the greater the resistance.
SEER	Seasonal Energy Efficiency Rating. It measures the efficiency of the air conditioner once it is up and running. Higher number is better.
SHGC	Solar Heat Gain Co-efficient. The solar radiation entering a home through the windows. The lower the number, the better the window is at blocking heat gain.
THERMAL ENVELOPE/ ENCLOSURE	A home's exterior shell – walls, foundation, floors, ceiling, windows, doors and roof.
U-VALUE	A measure of heat transmission due to the air temperature difference from inside to outside. The lower the U-value, the better.
VOC's	Volatile Organic Compounds. The term covers a wide range of chemical compounds, some of which can be harmful.

In the 21st century if it's not green, it's just not a good investment.

DavidWeekleyHomes.com
Green

